



Model :
KDC-25/S

PRP		ESP		Standby	Voltage/Ph	Hz/rpm	PF
kW	kVA	kW	kVA	Amps			
20	25	22	28	40	400/3Ph	50/1500	0.8

Prime power


According to ISO8528-1, prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.

Standby power

According to ISO 8528-1, It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. No overload capability is available.

Diesel Generator Set

Engine Make /Model	Cummins 4B3.9G1
Alternator Make /Model	Brushless, self-exciting
Control Panel	Smartgen HGM6120N
Base Frame / Silent Canopy	Robust Structure/ Corrosion Resistant
Circuit Breaker Type	3pole MCCB (4P Available as option)
Built in Base Fuel Tank Capacity	8-10hrs (Silent)
Battery	Maintenance free Lead Acid



Fuel Consumption (L/H)

100% standby power	8.0
100% prime power	7.1
75% prime power	5.7
50% prime power	4.3

Dimension and Weight

Dimension	Open	Silent
Length (L)	1650mm	2100mm
Width (W)	750mm	965mm
Height (H)	1300mm	1300mm
Net Weight	690KG	900KG

§ Engine Specification: 4B3.9G1

Basic technical data	
No. of cylinders	4
Cylinder arrangement	In-line
Cycle	4 stroke
Induction system	Naturally Aspirated
Compression ratio	17.3:1
Bore	102mm
Stroke	120mm
Displacement	3.9L

Cooling system	
Coolant capacity-engine	7.2L
Maximum coolant friction head external to engine:	
-1500 rpm	28kPa
Maximum static head of coolant above engine crank centerline	14.0m
Standard Thermostat (Modulating) Range	82 - 95 °C
Minimum Pressure Cap	69 kPa
Maximum Top Tank Temperature for Standby / Prime Power	110 / 104 °C

Fuel system	
Injection system	BYCA
Governor type	Mechanical
Maximum restriction at lift pump	13.6 kPa
Maximum fuel inlet temperature	70 °C
Total drain flow (constant for all loads)	30 litre hour

Air intake system	
Maximum intake air restriction with heavy duty air cleaner:	
-Dirty element	6 kpa
-Clean element	4 kpa

Lubrication system	
Engine oil pressure for engine protection devices:	
— Idle speed(Minimum)	207kPa
— Governed speed(Maximum)	345kPa
Maximum oil temperature	121 °C
Maximum oil consumption	
Oil pan capacity-low/high	10.9 L

General installation	Prime power
Gross engine power output	24kw
Piston speed	6.0 m/s
Friction horsepower	8.2 kW
Engine water flow to engine	2.2 l/sec
Oil flow	32.9 l/sec
Exhaust gas flow	70 l/sec
Exhaust gas temperature	380 °C
Radiated heat to ambient	TBD
Heat rejection to coolant	25.9 kW
Heat rejection to fuel	TBD

§ Diesel engine
§ 4-stroke cycle
§ Water-cooled
§ 24V electrical system
§ Water separator filter

§ Dry air filter
§ Radiator with pusher fan
§ Mechanical governor
§ Hot parts protection
§ Moving parts protection

§ Water jacked heater (Optional)
§ Radiator water level sensor (Optional)
§ Oil heater (Optional)
§ Heavy duty air filter (Optional)

§ Alternator

Alternator	
Number of phase	3
Power factor (Cos Phi)	0.8
Poles	4
Winding Connections (standard)	Star-serie
Terminals	12
Insulation type	H class
Winding Pitch	2/3
IP rating	IP23
Excitation system	Self-excited
Bearing	Single bearing
Coating	Vacuum impregnation
Voltage regulator	A.V.R
Couping	Flexible disc

§ Controller

Configuration

- Emergency stop button
- Protection MCB
- Battery charger
- Integrated aviation plug
- ATS connection
- Digital control module



Main Features

- Automatic mains failure
- Engine control, Generator protection
- Built in alarms and warnings
- Remote Start operation available
- Daily / weekly / monthly exerciser
- Weekly operation schedule programs
- Fuel pump control
- Mains simulation
- Block heater control
- Field adjustable parameters
- Free MS-Windows Remote monitoring
- LED displays
- Configurable analogue inputs
- I/O expansion capability



§ Options

Engine

- Water Jacket Pre-heater
- Fuel heater

Alternator

- Winding Temp measuring Instrument
- Alternator Pre-heater
- PMG
- Anti-damp and anti-corrosion treatment
- Anti-condensation heater
- Winding and bearing RTD

Generator Sets

- Tools with the machine
- Extended range fuel tank
- Bunded fuel tank

Fuel System

- Low fuel level alarm
- Automatic fuel feeding system
- Fuel T-valves

Canopy

- Rental type Canopy
- Trailer

Control Panel

- Remote control panel
- ATS
- Synchronizing controller
- Adjustable ear th leakage relay