

Koten

Generating Power
SOLUTIONS





50Hz

400V

3PH

20 ~ 40kVA

| 3Phase Genset Specification 400/230V 50HZ/1500RPM | | | | | Engine Specification | | | | Alternator | Silent Type | | |
|---|-----|-----|-----|-----|----------------------|--------------------|-----|------------|------------------|--------------------|---------------|------------|
| Genset Model | PRP | | ESP | | Engine Model | Engine Prime Power | Cyl | Gov | Displacement (L) | Chinese Alternator | Dim (mm) | G.W. (Kgs) |
| | kW | Kva | kW | Kva | | | | | | | | |
| KDI-20 | 16 | 20 | 18 | 22 | JE493DB-04 | 21 | 4 | Mechanical | 2.54 | 184ES | 2000*860*1050 | 745 |
| KDI-25 | 20 | 25 | 22 | 28 | JE493DB-02 | 24 | 4 | Mechanical | 2.54 | 184FS | 2000*860*1050 | 770 |
| KDI-30 | 24 | 30 | 26 | 33 | JE493ZDB-04 | 28 | 4 | Mechanical | 2.54 | 184GS | 2200*860*1050 | 835 |
| KDI-40 | 32 | 40 | 35 | 44 | JE493ZLDB-02 | 38 | 4 | Mechanical | 3.86 | 184J | 2100*910*1130 | 1020 |

Standard reference Conditions

Ambient conditions of reference according to ISO 8528-1:2018 normative: 1000 mbar, 25°C, 30% relative humidity.

Weights and dimensions based on standard products. Illustrations may include optional equipment.

Technical data described in this catalogue correspond to the available information at the moment of printing.



60Hz

220V

3PH

25 ~ 45kVA

| 3Phase Genset Specification 127/220V 60HZ/1800RPM | | | | | Engine Specification | | | | Alternator | Silent Type | | |
|---|-----|-----|-----|-----|----------------------|--------------------|-----|------------|------------------|--------------------|---------------|------------|
| Genset Model | PRP | | ESP | | Engine Model | Engine Prime Power | Cyl | Gov | Displacement (L) | Chinese Alternator | Dim (mm) | G.W. (Kgs) |
| | kW | Kva | kW | Kva | | | | | | | | |
| KDI-20 | 20 | 25 | 22 | 28 | JE493DB-03 | 24 | 4 | Mechanical | 2.54 | 184E | 2000*860*1050 | 745 |
| KDI-25 | 24 | 30 | 26 | 33 | JE493DB-01 | 28 | 4 | Mechanical | 2.54 | 184FS | 2000*860*1050 | 770 |
| KDI-30 | 28 | 35 | 31 | 39 | JE493ZDB-03 | 34 | 4 | Mechanical | 2.54 | 184G | 2200*860*1050 | 835 |
| KDI-40 | 36 | 45 | 40 | 50 | JE493ZLDB-01 | 46 | 4 | Mechanical | 3.86 | 184H | 2100*910*1130 | 1020 |

Standard reference Conditions

Ambient conditions of reference according to ISO 8528-1:2018 normative: 1000 mbar, 25°C, 30% relative humidity.

Weights and dimensions based on standard products. Illustrations may include optional equipment.

Technical data described in this catalogue correspond to the available information at the moment of printing.